

Safety Data Sheet

Castaldo® LiquaFAST ICE® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

09/01/2020

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity Castaldo® LiquaFAST ICE® RTV Jewelry Molding Rubber Part B
Alternate Names Castaldo® LiquaFAST ICE® RTV Jewelry Molding Rubber Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet.
Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Goodwin Refractory Services Ltd
Spencroft Road, Newcastle-under-Lyme,
Staffordshire, ST5 9JE, United Kingdom

Emergency

24 hour Emergency Telephone No. Chem-Tel: 1-800-255-3924
Customer Service: +44 (0) 1782 66 36 00

2. Hazard identification of the product

2.1. Classification of the substance or mixture

STOT RE 2;H373 May cause damage to organs through prolonged or repeated exposure.
Specific Target Organs: (lungs)

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Warning

H373 May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet

Castaldo® LiguaFAST ICE® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

09/01/2020

[Prevention]:

P260 Do not breathe mist / vapors / spray.

[Response]:

P314 Get Medical advice / attention if you feel unwell.

[Storage]:

No GHS storage statements

[Disposal]:

No GHS disposal statements

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Cristobalite CAS Number: 0014464-46-1	25 - 50	STOT RE 1;H372	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. Immediately rinse mouth with water.

Safety Data Sheet

Castaldo® LiquaFAST ICE® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

09/01/2020

4.2. Most important symptoms and effects, both acute and delayed

Overview

May cause eye irritation with redness and tearing. May cause mild skin irritation. May cause gastrointestinal irritation with nausea, vomiting and diarrhea. Individuals with pre-existing skin disorders may be at increased risk from exposure.

5. Fire-fighting measures

5.1. Extinguishing media

Appropriate for surrounding fire.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Thermal decomposition may produce dangerous Oxides of carbon, hydrocarbons, organic acids and aldehydes.
Do not breathe mist / vapors / spray.

5.3. Advice for fire-fighters

Firefighters should wear full emergency equipment and an approved positive pressure self-contained breathing apparatus.

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Prevent entry into sewers and waterways, after product recovery - wash surface with water.

7. Handling and storage

7.1. Precautions for safe handling

Avoid contact with the eyes and skin. Wear protective clothing and equipment as described in Section 8. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Contact of the "Base" component with alkaline or acid substances could produce flammable hydrogen gas.

Safety Data Sheet

Castaldo® LiquaFAST ICE® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

09/01/2020

Store between 5 C and 26 C / 41 - 80 F in a dry, ventilated area. Protect packages from physical damage. See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0014464-46 -1	Cristobalite	OSHA	No Established Limit
		ACGIH	TWA: 0.025 mg/m3
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0014464-46 -1	Cristobalite	OSHA	Select Carcinogen: No
		NTP	Known: Yes; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes

Protective safety glasses recommended.

Skin

Wear overalls to keep skin contact to a minimum. Chemical Impervious Gloves

Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

Safety Data Sheet

Castaldo® LiquaFAST ICE® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

09/01/2020

9. Physical and chemical properties

Appearance	Blue Thick liquid
Odor	None
Odor threshold	Not Measured
pH	NA
Melting point / freezing point	NA
Initial boiling point and boiling range	300C
Flash Point	NA
Evaporation rate (Ether = 1)	NA
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: NA Upper Explosive Limit: NA
Vapor pressure (Pa)	NA
Vapor Density	NA
Specific Gravity	1.11 G/CM3
Solubility in Water	Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	NA
Decomposition temperature	NA
Viscosity (cSt)	NA
VOC %	NA
% Volatile (by volume)	NA

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

Safety Data Sheet

Castaldo® LiquaFAST ICE® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

09/01/2020

No data available.

10.4. Conditions to avoid

Oxides of carbon, hydrocarbons, organic acids and aldehydes.

10.5. Incompatible materials

Contact of the "Base" component with alkaline or acid substances could produce flammable hydrogen gas.

10.6. Hazardous decomposition products

Thermal decomposition may produce dangerous Oxides of carbon, hydrocarbons, organic acids and aldehydes.

11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Cristobalite - (14464-46-1)	No data available	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	2	May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet

Castaldo® LiquaFAST ICE® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

09/01/2020

Aspiration hazard	---	Not Applicable
-------------------	-----	----------------

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Cristobalite - (14464-46-1)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

14.1. UN number	DOT (Domestic Surface Transportation) Not Applicable	IMO / IMDG (Ocean Transportation) Not Regulated	ICAO/IATA Not Regulated
------------------------	--	---	-----------------------------------

Safety Data Sheet

Castaldo® LiquaFAST ICE® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

09/01/2020

14.2. UN proper shipping name Not Regulated Not Regulated Not Regulated

14.3. Transport hazard class(es) **DOT Hazard Class:** Not Applicable **IMDG:** Not Applicable **Air Class:** Not Applicable
DOT Label: --- **Sub Class:** Not Applicable

14.4. Packing group Not Applicable Not Applicable Not Applicable

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user
No further information

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

WHMIS Classification D2B

US EPA Tier II Hazards **Fire:**No

Sudden Release of Pressure:No

Reactive:No

Immediate (Acute):No

Delayed (Chronic):Yes

EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 302 Extremely Hazardous :

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

Crystalline Silica - Quartz

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

N.J. RTK Substances (>1%):

Cristobalite

Penn RTK Substances (>1%):

Safety Data Sheet

Castaldo® LiquaFAST ICE® RTV Jewelry Molding Rubber Part B



SDS Revision Date:

09/01/2020

Cristobalite

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H372 Causes damage to organs through prolonged or repeated exposure.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

Disclaimer: The information contained herein is considered accurate; however, Goodwin Refractory Services Ltd makes no warranty regarding the accuracy of the information. The user must determine the suitability of the product for the intended use and accepts all risk and liability associated with that use.

End of Document